



PRE-RELEASE INFORMATION

NEW

HF/VHF/UHF ALL MODE TRANSCEIVER IC-7110

*All band, all mode
for every operating environment.*



Photo is an image of in-vehicle use. Installation for in-vehicle use must comply with the applicable laws and regulations of each country.

HF/VHF/UHF ALL MODE TRANSCEIVER IC-7110



HF/50/70*/144/430/440 MHz ALL Mode Coverage

*70 MHz for only EUR version

Real-Time Spectrum Scope and Waterfall Display

CW Decoder

Comprehensive D-STAR Functionality

4.3-inch Large Color Display with Touch Operation

Dualwatch for HF/VHF and HF/UHF

Simple Configuration for FT8 Operation

Wi-Fi® (2.4 GHz / 5 GHz) and Bluetooth® Connectivity

D-STAR



Promotion Video

HF/50/70*/144/430/440 MHz ALL Mode Coverage

Enjoy a wide range of bands—from HF to 50/VHF/UHF MHz—in SSB, CW, RTTY, AM, FM, and D-STAR DV mode. The IC-7110 delivers 100 W output on HF/50 MHz and 50 W on VHF/UHF. FM broadcast and airband reception also supported.

Dualwatch for HF/VHF and HF/UHF

The receiver section incorporates independent circuits for HF/50 MHz and VHF/UHF, enabling true dual-watch operation. Operating modes can be set independently for each band. You can enjoy operation on VHF or UHF while monitoring HF band conditions supporting advanced multi-band operation.



Simple Configuration for FT8 Operation

FT8 operation is made easier with the simplified FT8 preset. Selecting FT8 from the [Preset] menu automatically configures all required parameters. Switching back to normal operation is just as simple—select [Normal]. Presets 3–5 can store new preset information, allowing future digital modes, such as SSTV, to be supported.



Wi-Fi® (2.4 GHz / 5 GHz) and Bluetooth® Connectivity

Wi-Fi® provides smooth Internet access for Terminal and Access Point modes, with stable performance. The unit connects wirelessly to a smartphone or PC for easy app use, and pairing with a Bluetooth® headset enables flexible hands-free operation. Features online updates for D-STAR repeater lists and firmware via Wi-Fi®.

Controller



- 1 USB Type-C™ port
- 2 microSD Card Slot
- 3 AMPS Hole Pattern
- 4 Magnet for Optional Accessories
- 5 1/4-20 Tripod Mount
- 6 Microphone Connector
- 7 Main Unit Connection Port
- 8 Electronic Keyer Jack
- 9 Headphone Jack

Real-Time Spectrum Scope and Waterfall Display

The IC-7110 features a real-time spectrum scope and waterfall display. The real-time scope allows quick identification of open frequencies, band conditions, and rapid access to target signals. The waterfall display provides a graphical view of how received signals change over time.



CW Decoder

The IC-7110 includes the highly acclaimed CW decoder from the IC-7300MK2. Settings include decode key speed (AUTO, LOCK, KEY SPEED link), decode filter (AUTO, FIX), and threshold (AUTO, MANUAL), allowing customization to suit operating conditions.




Note: Decoding accuracy may vary depending on reception conditions.

Comprehensive D-STAR Functions

The IC-7110 offers a full suite of D-STAR features, including DR mode, Terminal/Access Point mode, and DV repeater monitor. Picture transmission, reception, and viewing are possible directly on the IC-7110 without external devices.



Main Unit



- 10 Electronic Keyer Jack
- 11 HF/50 MHz antenna connector
- 12 144/430 MHz antenna connector
- 13 GND Terminal
- 14 Microphone Connector
- 15 External Speaker Jack
- 16 Remote Jack
- 17 DATA1 Jack
- 18 USB Type-C™ Port
- 19 ACC Socket
- 20 DATA2 Socket
- 21 Controller Connector
- 22 Tuner Connector
- 23 DC Power Input Connector

This device has not been approved by the appropriate authorities in each country. This device may not be sold or leased, or be offered for sale or lease, until approval has been obtained. All stated features, appearances, screen shots and specifications may be subject to change without notice. Icom and the Icom logo are registered trademarks of Icom Incorporated (Japan) in Japan, the United States, the United Kingdom, Germany, France, Spain, Russia, Australia, New Zealand and/or other countries. The Bluetooth® word mark and logos are registered trademarks owned by Bluetooth SIG, Inc. and any use of such marks by Icom Inc. is under license. Wi-Fi is a registered trademark of Wi-Fi Alliance®. All other trademarks are the properties of their respective holders.

Icom Inc. 1-1-32, Kamiminami, Hirano-ku, Osaka 547-0003, Japan Phone: +81 (06) 6793 5302 For the latest information, please visit www.icomjapan.com

- Icom America Inc. www.icomamerica.com
- Icom Canada www.icomamerica.com
- Icom Brazil www.icomamerica.com
- Icom (Europe) GmbH www.icomeurope.com
- Icom Spain S.L. www.icomspain.com
- Icom (UK) Ltd. www.icomuk.co.uk
- Icom France s.a.s. www.icomfrance.com/fr/
- Icom (Australia) Pty. Ltd. www.icom-australia.com
- Icom Asia Co., Ltd. www.icomasia.com