



VHF MARINE TRANSCEIVER

IC-M90E

Commercial Grade Marine & Private Mobile Radio



Waterproof
1m depth for 30 minutes

Wide LCD allows wide viewing angles

A wide viewing angle, high intensity LCD is used in the IC-M90E, offering bright, easy to read characters. The LCD's contrast and backlight are adjustable in 4-levels*. The LED indicator on top of the front panel shows the operating status clearly.

* Backlight includes OFF setting.

Built-in Voice scrambler

A built-in 32 code voice scrambler, compatible with the UT-112, provides privacy in secret conversation.

100 programmable channels for PMR use

The IC-M90E is suitable for both marine and private mobile applications. Up to 100 programmable channels are available for private mobile use (146-174MHz)*. CTCSS and DTCS tone signalings and wide/narrow channel bandwidth are programmable for each channel. (12.5/25kHz or 12.5/20kHz).

* Appropriate license will be required. Ask your dealer for details.

Optional VOX (Voice Operated Transmit) headset

With one of Icom's optional headsets* and the OPC-1392, the IC-M90E offers hands-free operation.

* See options listed on back.

Waterproof speaker microphone, HM-125*

* Optional, equivalent to IPX7.
(1m depth for 30 minutes)

Tough and waterproof for heavy-duty use

The IC-M90E is a waterproof (IPX7*), reliable, commercial grade radio. It's simple, yet rugged construction has a polycarbonate casing with an insert-type battery to prevent water intrusion. A newly developed "speed water removal" system removes water from the speaker grill to prevent distortion in received audio.

* Equivalent to IPX7 of the corresponding International Standard IEC 60529 (2001). 1m depth for 30 minutes.

Long wear printed buttons

Clearly labeled large buttons and positive button action allows for operation in all conditions, even when wearing heavy gloves. The transparent buttons are printed from behind (not on top), so the operating label on the keypad will never be erased under hard use over many years.

Icom Inc.

ADDITIONAL FEATURES

- Instant access to Ch. 16 and call channel
- Simple add/delete TAG scanning operation
- Monitor button opens squelch
- Automatic scan function
- 2 step power save mode for longer battery life
- Battery indicator shows remaining battery power in 4 levels
- Beep sound is programmable for each button
- Self check function
- Key lock function

SPECIFICATIONS

GENERAL		TRANSMITTER		RECEIVER	
• Frequency range	: Marine Tx 156.000-161.450MHz Rx 156.000-163.425MHz PMR Tx/Rx 146.000-174.000MHz	• Output power (Hi/Mid/Low)	: 5/3/1W FRG version 1/0.5W (Marine) 5/3/1W (PMR)	• Sensitivity (20dB SINAD)	: Marine -2dBμ emf typical PMR -4dBμ emf typical
• Usable channels	: INT, USA* channels; 100 programmable channels (* Depending on version)	• Max. frequency deviation	: Marine ± 5.0kHz PMR (W/N) ± 5.0/2.5kHz FRG version (M/N) ± 4.0/2.5kHz	• Squelch sensitivity	: 0dBμ emf typical (threshold)
• Channel spacing	: Marine 25kHz PMR 25/12.5kHz FRG version 20/12.5kHz	• Audio harmonic distortion	: Less than 10% (at 60% dev.)	• Adjacent channel selectivity	: Marine 70dB PMR (Wide/Narrow) 70/60dB
• PLL channel step (PMR)	: 5/6.25/7.5kHz	• Frequency error	: ± 1.5kHz	• Spurious response	: 70dB
• Current drain (at 7.2V DC)	: Tx 5W output 1.6A typical Rx AF max. 200mA typical	• Spurious emissions	: Less than 0.25μW (below 2GHz)	• Intermodulation rejection	: Marine 68dB PMR 65dB
• Operating temperature range	: Marine -15°C to +55°C PMR -25°C to +55°C	• Adjacent channel power	: Marine 70dB PMR (Wide/Narrow) 70/60dB	• Hum and noise ratio	: Marine 40dB PMR (Wide/Narrow) 40/34dB
• Antenna impedance	: 50Ω (SMA)	• Hum and noise ratio	: Marine 40dB PMR (Wide/Narrow) 40/34dB	• Audio output power (at 10% distortion with an 8Ω load)	: Marine 0.2W PMR 0.35W
• Dimensions (W×H×D)	: 65×145×44 mm (projections not included)	<p>Supplied accessories: (* Varies according to version.)</p> <ul style="list-style-type: none"> • Battery pack, BP-225 • Battery charger, BC-158* • AC adapter, BC-147E* • Belt clip, MB-103 • Antenna, FA-S59V • Hand strap 			
• Weight (approx.)	: 410g (with BP-225)				

Measurements made in accordance with EN301 178 or EN300 086. All stated specifications are subject to change without notice or obligation.

OPTIONS

Some options may not be available in some countries. Please ask your dealer for details.

- BP-223 BATTERY CASE**
Battery case for AA (LR6)×6 alkaline cells.
- BP-224/BP-225 BATTERY PACKS**
BP-224: 7.2V/750mAh Ni-Cd battery pack.
BP-225: 7.2V/1100mAh Ni-Cd battery pack.
Provides 7, 10 hours operating time* respectively (approx. at 5 Watts).
* Tx (Hi): Rx: standby=5:5:90
- BC-158 DESKTOP CHARGER**
+ **BC-147E AC ADAPTER**
Regularly charges the BP-225 in 12-18 hours. Same as supplied.
- BC-119N DESKTOP CHARGER**
+ **AD-109 CHARGER ADAPTER**
+ **BC-145E AC ADAPTER**
For rapid charging of battery pack. An AC adapter is supplied depending on version. Charges the BP-225 within 2.2-2.8 hours.
- BC-121N MULTI-CHARGER**
+ **AD-109 CHARGER ADAPTER**
+ **BC-124 AC ADAPTER**
For rapid charging of up to 6 battery packs (Six AD-109s are required). Charges the BP-225 2.2-2.8 hours.
- CP-17L CIGARETTE LIGHTER CABLE**
WITH NOISE FILTER
OPC-515L DC POWER CABLE
For use with the BC-119N or BC-158 with an external DC power supply. (12-16 V DC required)
- OPC-656 DC POWER CABLE**
For use with the BC-121N with a DC power supply. (12-16V DC required)
- MB-86 SWIVEL BELT CLIP**
MB-103 BELT CLIP
Alligator type. Same as supplied.
- HM-125 SPEAKER-MICROPHONE**
Full sized, waterproof construction corresponds to IPX7 (1 m depth for 30 min.).
- HS-94 EARPHONE-HEAD HEADSET**
HS-95 BEHIND-THE-HEAD HEADSET
HS-97 THROAT MICROPHONE
+ **OPC-1392 HEADSET ADAPTER CABLE**
For VOX, hands-free operation. These headsets are not waterproof.



Icom Inc. 1-1-32, Kamiminami, Hirano-ku, Osaka 547-0003, Japan Phone: +81 (06) 6793 5302 Fax: +81 (06) 6793 0013 URL: <http://www.icom.co.jp/world/index.html> **Count on us!**

Icom America Inc.
2380 116th Avenue N.E., Bellevue, WA 98004, U.S.A.
Phone: +1 (425) 454-8155
Fax: +1 (425) 454-1509
E-mail: sales@icomamerica.com
URL: <http://www.icomamerica.com>
<Customer Service> Phone: +1 (425) 454-7619

Icom Canada
Glenwood Centre #150-6165 Highway 17, Delta, B.C., V4K 5B8, Canada
Phone: +1 (604) 952-4266
Fax: +1 (604) 952-0090
E-mail: info@icomcanada.com
URL: <http://www.icomcanada.com>

Icom New Zealand
146A Harris Road, East Tamaki, Auckland, New Zealand
Phone: +64 (09) 274 4062
Fax: +64 (09) 274 4708
E-mail: inquiries@icom.co.nz
URL: <http://www.icom.co.nz>

Icom (Europe) GmbH
Communication Equipment Himmelgeister Str. 100, D-40225 Düsseldorf, Germany
Phone: +49 (0211) 346047
Fax: +49 (0211) 333639
E-mail: info@icom-europe.com
URL: <http://www.icomeurope.com>

Icom (UK) Ltd.
Unit 9, Sea St., Herne Bay, Kent, CT6 8LD, U.K.
Phone: +44 (01227) 741741
Fax: +44 (01227) 741742
E-mail: info@icomuk.co.uk
URL: <http://www.icomuk.co.uk>

Icom France S.a
Zac de la Plaine, 1, Rue Brindejone des Moulinais BP 5804, 31505 Toulouse Cedex, France
Phone: +33 (5) 61 36 03 03
Fax: +33 (5) 61 36 03 00
E-mail: icom@icom-france.com
URL: <http://www.icom-france.com>

Asia Icom Inc.
6F No. 68, Sec. 1 Cheng-Teh Road, Taipei, Taiwan, R.O.C.
Phone: +886 (02) 2559 1899
Fax: +886 (02) 2559 1874
E-mail: sales@asia-icom.com
URL: <http://www.asia-icom.com>


Beijing Icom Ltd.
1305, Wanshang Plaza, Shijingshan Road, Beijing, China
Phone: +86 (010) 6866 6337
Fax: +86 (010) 6866 3553
E-mail: bjicom@bjicom.com
URL: <http://www.bjicom.com>

Your local distributor/dealer:

Icom (Australia) Pty. Ltd.
A.B.N. 88 006 092 575
290-294 Albert Street, Brunswick, Victoria, 3056, Australia
Phone: +61 (03) 9387 0666
Fax: +61 (03) 9387 0022
E-mail: sales@icom.net.au
URL: <http://www.icom.net.au>

Icom Spain S.L.
Ctra. de Gracia a Manresa Km. 14,750 08190 Sant Cugat del Valles Barcelona, Spain
Phone: +34 (93) 590 26 70
Fax: +34 (93) 589 04 46
E-mail: icom@icomspain.com
URL: <http://www.icomspain.com>

Icom Polska
Sopot, 3 maja 54, Poland
Phone: +48 (58) 550 7135
Fax: +48 (58) 551 0484
E-mail: icompolska@icompolska.com.pl
URL: <http://www.icompolska.com.pl>



Icom Inc. (Japan), is an ISO 9001 and ISO 14001 certification acquired company.